

ISO 9001

CERTIFIED QUALITY



CERTIFIED DEPENDABILITY



Bronze globe valve

317 fig BGC-17

Stock code VGBS317IB

Complete with internal bonnet, back seat for repacking under pressure bronze seat, Teflon clack and spindle.

Suitable for 125PSI (860kPa) steam or 200PSI (1400kPa) water, oil or gas.

Sizes 1/2" to 2" (15mm to 50mm).



Bronze globe valve

317 fig BG-22V

Stock code VGTS317

Complete with union bonnet, back seat for repacking under pressure, replaceable Teflon clack, and bronze seat and spindle.

Suitable for 150PSI (1000kPa) steam or 225PSI (1550kPa) water, oil or gas.

Sizes 1/2" to 2" (15mm to 50mm).



Bronze safety valve

317 fig SV-S69

Stock code VSASSS317

Complete with bronze body and easing lever, stainless steel seat, clack and spring.

Suitable for 150PSI (1000kPa) steam, water and or gas at 200°C.

Sizes 1/2" to 2" (15mm to 50mm)



Cast iron thermodynamic steam trap

317 fig ST-T3A

Stock code VSTTDS317

Complete with stainless steel seat, disc and built in strainer.

Suitable for 250PSI (1600kPa) steam.

Temperature 220°C

Sizes 1/2" to 2" (15mm to 50mm)



Cast iron y-type strainer

317 fig SV-S69

Stock code VSS317

Complete with bronze body and easing lever, stainless steel seat, clack and spring.

Suitable for 150PSI (1000kPa) steam, water and or gas at 200°C.

Sizes 1/2" to 3" (15mm to 80mm)

ISO 9001

CERTIFIED QUALITY



CERTIFIED DEPENDABILITY



Cast iron sight glass


317 fig SK-B1

Stock code VSCCI317

The double window allows for easy viewing in the dark by holding a torch underneath the valve and shining it through both windows.

Suitable for 100PSI (700kPa) steam or 150PSI (1000kPa) water, oil or gas at 220°C

Sizes ½" to 2" (15mm to 50mm)



Cast iron ball float valve

317 fig FT-551

Stock code VBFF317

Complete with stainless steel internals, stainless steel float and arm.

Suitable for 150PSI (1000kPa) water at 100°C.

Sizes 2" to 8" (50mm to 200mm).



Bronze gauge glass column

317 fig BG-WGV

Stock code VGG317

Complete with rubbers. Spare NBR rubbers available.

Suitable for 100PSI (690kPa) steam, water or non-corrosive fluids.

Sizes ½" to ¾" (15mm to 20mm).



Stainless steel gauge glass column

317 fig WGVSS

Stock code VGGSS317

Complete with viton rubbers. Spare viton seals available.

Suitable for 100PSI (690kPa) fluids related to CF8M stainless steel.

Sizes ½" to ¾" (15mm to 20mm)



Cast iron sight check

317 fig SK-T8

Stock code VSCC1SW317

Complete with Teflon ball and single window sight glass.

Suitable for 100PSI (700kPa) steam, water, oil or gas at 220°C.


Sizes ½" to 2" (15mm to 50mm)

ISO 9001

CERTIFIED QUALITY



CERTIFIED DEPENDABILITY



Cast iron pressure reducing valve


317 fig PR3AS

Stock code VRS317

Complete with stainless steel seat, clack and diaphragm. Full range of spares available including diaphragms, seals and plungers.

Suitable for 150PSI (1000kPa) steam, water, oil or gas at 200°C.

Sizes ½" to 2" (15mm to 50mm).



Bronze pressure reducing valve

317 fig PR-B6S

Stock code VRARS317

Complete with stainless steel seat and replaceable o'ring on a metal piston diaphragm. Suitable for 250PSI (1600kPa) water, oil and non-corrosive fluids at 70°C.

Sizes ½" to 2" (15mm to 50mm).



Cast iron flanged PN16 undrilled relief valve

317 fig S3F-A

Stock code VRFCI317

Complete with cast iron body, 304 stainless steel seat clack and spindle. Suitable for 150P.S.I (1000kPa) Water, oil or gas. Flanged PN16 undrilled.

Sizes: 2", 3" and 4" (50mm, 80mm and 100mm)



Cast iron flanged PN16 undrilled safety valve

317 fig S3F-LR

Stock code VSFCI 317

Complete with cast iron body and lever. 304 Stainless steel seat clack and spindle.

Suitable for 150P.S.I (1000kPa) Steam, air or gas. Flanged PN16 undrilled.

Sizes: 2", 3" and 4" (50mm, 80mm and 100mm)