



for safety that's a pressure relief!



Bronze safety valve

SS fig S10L

Stock code VSAS317

Complete with bronze seat, clack and easing lever.

Suitable for 150PSI (1000kPa) steam, water, oil or gas at 200°C.

Sizes ½" to 2" (15mm to 50mm).



Bronze relief valve

SS fig S10

Stock code VRARSS

Complete with bronze seat and clack.

Suitable for 150PSI (1000kPa) steam, water, oil or gas at 200°C.

Sizes ½" to 2" (15mm to 50mm).



Bronze safety valve

SS fig FGXLBSS

Stock code VSFGXLBSS

Complete with high lift stainless steel seat, clack, stainless steel spring, and metal easing lever.

Suitable for 580PSI (4000kPa) steam, water, oil or gas at -196°C to 350°C.

Sizes ½" to 2" (15mm to 50mm)



Bronze relief valve

SS fig FGXBSS

Stock code VRFGXBSS

Complete with high lift pop type stainless steel seat and clack.

Suitable for 580PSI (4000kPa) steam, water, oil or gas at -196°C to 350°C.

Sizes ½" to 2" (15mm to 50mm)



for safety that's a pressure relief!



Stainless steel safety valve

SS fig FGXLSSS

Stock code VSFGXLSSS

Complete with high lift 316 stainless steel seat, clack, spring, and metal easing lever.

Suitable for 580PSI (4000kPa) steam, water, oil or gas at -196°C to 350°C .

Sizes $\frac{1}{2}$ " to 2" (15mm to 50mm)



Stainless steel relief valve

SS fig FGXSSS

Stock code VRFGXSSS

Complete with stainless steel seat, clack and spring (CF8M).

Suitable for 580PSI (4000kPa) steam, water, oil or gas or fluids related to CF8M stainless steel at -196°C to 350°C .

Sizes $\frac{1}{2}$ " to 2" (15mm to 50mm)



Brass pop type relief valve

SS fig HOP411A

Stock code VRHOP411A

Complete with stainless steel ball, brass seat and pull type test action.

Suitable for 150PSI (1000kPa) compressed air systems.

Sizes $\frac{1}{4}$ " to 1" (8mm to 25mm).